

13 Registration

13.1 Introduction

This clause specifies the rules and guidelines that have been used in the specification of the concepts in this International Standard, and shall be followed in preparing registration proposals. Registration proposals include required information for new SRM registered items, as well as accompanying administrative information (see [Annex H](#)). The guidelines in [13.2](#) shall apply to all SRM registered items. Additional guidelines applicable to specific SRM concepts are specified in [13.3](#).

[ISO/IEC 9973](#) allows for previously registered items to be added to this International Standard, when amended. When previously registered SRM concept instances are added to this International Standard, all abbreviations used (in labels, description text, etc.) in those instances that are not already included in [Table 3.3](#) and/or [Table F.1](#) shall be added, as appropriate. Additionally, all associated references (see [13.2.5](#)) not already included in [Clause 2](#) or the [Bibliography](#) shall be added, as appropriate.

13.2 Specification elements for SRM registered items

13.2.1 Introduction

The specification of each SRM registered item shall include the following elements:

- a) label: a unique, compact, character string that is used to denote the registered item,
- b) code: a unique integer³⁰ that is assigned by the registration authority to denote the registered item, and
- c) other concept-dependent information that may include the following elements:
 - 1) a description, and
 - 2) references.

In specifying an SRF set, assigning labels to the set members is optional (see [8.7.1](#)).

13.2.2 Label

The *label* element of an SRM registered item specification shall be a compact and human-readable designator that is used to denote that registered item. Labels in this International Standard may include the name or names for the registered item.

Each label in this International Standard shall:

- a) uniquely denote a specific instance within the set of instances of a given SRM concept,
- b) be a succinct expression of the concept instance that it denotes,
- c) be represented as a character string, and
- d) be human readable.

For presentation purposes only, a long label may be displayed on more than one line by using a hyphen (-) to separate the label before an underscore (_) character.

³⁰ Uniqueness is only within the set of instances of each SRM concept, for example: RDs or ORMs.

EXAMPLE 1 The label LOCOCENTRIC_SURFACE_EUCLIDEAN may be displayed for presentation purposes as:
LOCOCENTRIC_SURFACE -
_EUCLIDEAN.

If two concept instances differ only in the dimension of an associated position-space or the dimension of an associated object-space, then the characters “_1D”, “_2D”, or “_3D”, as appropriate, shall be appended to the label as a means of differentiating such concept instances.

Labels shall be presented, in this International Standard or in other documents, such that it is clear which SRM concept is represented. This is achieved by preceding the label with the concept abbreviation, which identifies the concept context.

EXAMPLE 2 The label TRANSVERSE_MERCATOR is used as both an SRFT and a CS label. Each of these shall be presented as shown below.

SRFT [TRANSVERSE_MERCATOR](#)
CS [TRANSVERSE_MERCATOR](#)

The labels of standardized SRM concept instances in this International Standard were created by applying the following guidelines. Labels for proposed SRM items shall be created according to these guidelines:

- a) A label shall be provided for each registered SRM concept instance.
- b) Labels shall be character strings.
- c) Labels shall contain only uppercase characters (A-Z) and digits (0-9) with the exception of the radix delimiter symbol "r" and the underscore character (_).
- d) Labels shall begin with an uppercase alphabetic character (A-Z).
- e) Labels shall not contain spaces.
- f) Labels may be a single word or abbreviation (see [3.2](#) and [Annex F](#)), or may be composed of a series of components, each of which is a word or an abbreviation.
- g) The underscore (_) character shall be used to concatenate the components of a label.
- h) Labels should be as short as possible while capturing a common use descriptive word or phrase representative of the registered SRM concept instance.
- i) The length of a label shall not exceed sixty-three (63) characters, and should be unique within the first thirty-one (31) characters.

The components of a registered SRM concept instance label shall be chosen according to the following guidelines:

- a) Components of labels shall not be used with a different meaning from how that component is used in this International Standard or in previously registered SRM concept instances.
- b) When abbreviating, if a word or phrase to be abbreviated appears in [Annex F](#) or [Table 3.3](#), the given abbreviation for that word or phrase shall be used.
- c) When abbreviating, if a word or phrase to be abbreviated does not appear in [Annex F](#) or [Table 3.3](#), the proposed abbreviation should, if possible, be consistent with those specified in [Annex F](#) and [Table 3.3](#).

Recognized abbreviations for words or phrases may be used as components of a label based on the following guidelines:

- a) Each abbreviation shall uniquely represent a single word or phrase.
- b) If a word or phrase is abbreviated in one label, it is not required to be abbreviated in other labels.

- c) Jargon shall not be used.
- d) An abbreviation in a label shall not be, by itself, a word with a different meaning than that of the word/phrase that it replaces.

EXAMPLE 3 The abbreviation DATUM should not be used for the phrase "Dartmouth Arc Transit Universal Meridian" as this would violate guideline (d).

13.2.3 Code

The *code* element of an SRM registered item specification shall be a compact designator that is used to uniquely identify that registered item. Codes are assigned by the registration authority for this International Standard when a registration proposal is accepted. Therefore, codes are not included in registration proposals.

Each code in this International Standard shall:

- a) uniquely denote a specific instance within the set of instances of a given SRM concept,
- b) be represented as an integer, and
- c) be assigned sequentially in increasing order within the set of instances of a given SRM concept, beginning at 1.

There is a one-to-one relationship between labels and codes in the same set of SRM concept instances. Therefore, a label and a code may be used interchangeably to denote the same concept instance. The set of members of a single SRF set shall be considered as a separate and distinct set from the set of members of a different SRF set.

Application program interfaces and exchange formats often utilize codes. Applications using such codes shall be capable of distinguishing $2^{31}-1$ different codes. Negative codes are not permitted in this International Standard, but they may be used in a non-conforming implementation for experimentation. The code value zero is reserved for use in the API (see [Clause 11](#)).

All codes for SRM standardized concept instances that are not assigned in this International Standard are reserved for future standardization or for registration. Codes shall be assigned by the registration authority for this International Standard according to these rules:

- a) Nothing shall be assumed about the relationship among standardized or registered SRM concept instances from the numerical relationships of their corresponding codes. In particular, the numerical sequencing of codes does not impose any sequential ordering to the standardized or registered SRM concept instances denoted by those codes.
- b) Integers are used to represent codes even though only positive integer values shall ever be assigned in either this International Standard or through registration. This allows negative integer values to be used experimentally in applications, even though such use of negative integer values is not in conformance to this International Standard.
- c) The registration authority for this International Standard shall assign codes in increasing order beginning at the first available integer value, and skipping no integer values, within the set of codes for each SRM concept.
- d) The registration authority for this International Standard shall coordinate the assignment of codes with future revisions of this International Standard to ensure that no code shall be assigned more than once in the same scope by either standardization or registration.

13.2.4 Description

The contents of the *description* element of an SRM registered item specification shall be a precise statement of the nature, properties, scope, and/or essential qualities of the concept instance.

The descriptions of standardized SRM concept instances in this International Standard were created by applying the following guidelines. Descriptions for proposed SRM items shall be created according to these guidelines:

- a) A description shall be provided for each SRM concept instance. This description shall contain at least one word, number, expression or formula.
- b) Descriptions shall be clear and concise, containing only the content necessary to summarize the concept instance.
- c) Jargon shall not be used.
- d) When abbreviating, if a word or phrase to be abbreviated appears in [Table 3.3](#), the given abbreviation for that word or phrase shall be used.
- e) When abbreviating, if a word or phrase to be abbreviated does not appear in [Table 3.3](#), the proposed abbreviation should, if possible, be consistent with those specified in [Table 3.3](#).

13.2.5 References

13.2.5.1 Introduction

Two types of references are recognized in International Standards. The first type of reference is a normative reference (see [ISO/IEC Directives, Part 2](#)). Identified provisions of a normative reference are incorporated by reference and "become" part of the subject standard. Normative references play a key role in ensuring the consistency of the body of International Standards by allowing work done by others to be reused without modification. The second type of reference is an informative reference (see [ISO/IEC Directives, Part 2](#)). Identified provisions of an informative reference are cited as being the source of, related to, or providing additional information about text in the subject standard, but the identified provisions of the document are not themselves directly incorporated into the subject standard.

13.2.5.2 Citation format

Each citation consists of an identifier and an optional location enclosed in square brackets ([]) with the identifier listed first, followed by a comma, followed by the location. The identifier specifies the cited document and shall appear in either [Clause 2](#) or the [Bibliography](#). The location specifies the portion of the document that is cited. Whenever possible, the location shall be specified in accordance with the requirements in [ISO/IEC Directives, Part 2](#). When a cited document lacks a subclause structure, the location may be specified in a convenient and natural format depending on the organization of the cited document.

EXAMPLE [\[83502T](#), App. A-1, "HO"] and [\[RIIC06](#), Table 4, "Saturn"].

13.3 Guidelines for specific SRM concepts

13.3.1 Guidelines for registration of abstract CSs

Abstract CSs shall be registered according to the following additional guidelines:

- a) The function type shall be either "generating function" or "map projection".
- b) The CS descriptor shall be one of: 3D linear, 3D curvilinear, surface linear, surface curvilinear, map projection, 2D linear, 2D curvilinear, 1D linear, 1D curvilinear, or surface (map projection) and 3D (augmented map projection).
- c) The CS properties shall be either "none" or a list of one or more properties of the CS chosen from the following: orthogonal, not orthogonal, orthonormal, not orthonormal, conformal, or not conformal. Conformal and not conformal only apply to map projections.

- d) The CS parameters and constraints, if any, shall specify the parameters of the CS and the constraints on how those parameters interrelate.
- e) The coordinate-component symbols and common names shall specify these symbols and terms as used in the specification of coordinates in the CS. Thus in the case of the geodetic CS, " λ : longitude in radians, φ : latitude in radians, and h : ellipsoidal height".
- f) The domain of the CS generating function or mapping equations shall be specified in terms of the coordinate-components and other CS parameters.
- g) The CS generating function or mapping equations shall be specified in terms of the coordinate-components and other CS parameters. In the case of an oblate ellipsoid, common parameters and functions from [Table 5.6](#) shall be used if possible.
- h) The domain of the inverse of the CS generating function or mapping equations shall be specified in terms of the coordinate-components and other CS parameters.
- i) The inverse of the CS generating function or mapping equations shall be specified in terms of the coordinate-components and other CS parameters. In the case of an oblate ellipsoid common parameters and functions from [Table 5.6](#) shall be used.
- j) If the CS is a map projection, the convergence of the meridian function shall be specified in terms of the coordinate-components, other CS parameters, and or functions from [Table 5.6](#).
- k) If the CS is a map projection, the point distortion function(s) shall be specified in terms of the coordinate-components, other CS parameters, and or functions from [Table 5.6](#).
- l) Supplementary geometric figures may be provided that explain the roles of the CS parameters and illustrate the CS.
- m) Additional, non-normative information concerning the CS may be supplied in the form of notes.

EXAMPLE 1 Guideline d:

CS parameters:	" a : major semi-axis length, and b : minor semi-axis length" and
CS parameter constraints:	" $a > b$ ".

EXAMPLE 2 Guidelines f and h: " $-\pi/2 < \varphi < \pi/2$, $-\pi \leq \lambda < \pi$, and $-b < h$ ".

EXAMPLE 3 Guideline m note: "The generating function is the composition of the generating function for azimuthal spherical with the 3D localization operator."

13.3.2 Guideline for registration of temporal CSs

Temporal CSs shall be registered according to the additional guideline that the description of the temporal CS, including any common name, shall be specified.

13.3.3 Guidelines for registration of RDs

RDs shall be registered according to the following additional guidelines:

- a) The name of the physical object, if any, shall be specified.
- b) If the RD is not based on an ellipsoid, the analytic formulation of the RD in position-space shall be specified.

- c) If the RD is based on an ellipsoid, the parameter values shall be specified as follows:
 - 1) For an RD based on an oblate ellipsoid: major semi-axis, a , and flattening, f .
 - 2) An RD based on a sphere shall be specified as an oblate ellipsoid RD with major semi-axis equal to the sphere radius and the flattening equal to zero.
 - 3) For an RD based on a prolate ellipsoid: minor semi-axis, a , and major semi-axis, b .
 - 4) For an RD based on a tri-axial ellipsoid: semi-axis, a , semi-axis, b , and semi-axis, c .
- d) RD parameters shall be specified by value or by reference (see [13.2.5](#)).
 - 1) If by value, the value(s) shall be specified and followed by an error estimate expressed in one of the following forms:
 - i) error estimate: unknown
 - ii) error estimate: assumed precise
 - iii) error estimate (1σ): <parameter name>:<error value>
 - iv) error interval: <parameter name> \pm <error value>
 - 2) If by reference, this element shall contain a citation(s) for the value(s) and error estimate(s) using the terminology found in the reference. These terms shall be enclosed in brackets ({ }). Any parameter value that is not specified in the citation(s) shall be specified as in the “by value” case.
- e) The date the RD parameters were specified or published shall be specified.

EXAMPLE 1 Guideline b: “ $F(t) = t(0,0,1)$ ”.

EXAMPLE 2 Guideline c.1: “ $a = 6\,377\,563,396$ ” and “ $f = 1/299,324\,964\,6$ ”.
 Guideline c.2: Sphere of radius 6 371 229 specified as “ $a = 6\,371\,229$ ” and “ $f = 0$ ”.
 Guideline c.3: “ $a = 4\,564$ ” and “ $b = 4\,608$ ”.
 Guideline c.4: “ $a = 581\,100$ ”, “ $b = 577\,900$ ”, and “ $c = 577\,700$ ”.

EXAMPLE 3 Guideline d.1.iii: “error estimate (1σ): $a : 1\,250$, $f^{-1} : 0,25$ ”.

13.3.4 Guidelines for registration of STTs

STTs shall be registered according to the following additional guidelines:

- a) The dimension shall be specified as either “2D” or “3D”.
- b) The STT parameters and constraints, if any, shall specify the parameters of the STT and constraints on how those parameters interrelate. STT parameter symbols shall be listed in a specified order each having a name, optionally a description, and a unit of measure (or unitless).
- c) The STT formulation and inverse formulation shall be specified in terms of the STT parameters and the source and target positions.
- d) Additional, non-normative information concerning the STT may be supplied in the form of notes.

EXAMPLE 1: Guideline b:

STT parameters:

Δx : the x -component of the origin displacement in metres.

Δy : the y -component of the origin displacement in metres.

Δz : the z -component of the origin displacement in metres.

ω_1 : x -axis rotation in radians.

ω_2 : y -axis rotation in radians.

ω_3 : z -axis rotation in radians.

Δs : scale difference from unity (unitless).

Constraints:

1) ω_1 , ω_2 and ω_3 are small rotations (magnitude less than 2×10^{-4} radians) in the position vector rotation convention.

2) Δs is a small adjustment of scale ($|\Delta s| < 10^{-5}$).

EXAMPLE 2: Guideline c:

STT formulation:

$$\begin{pmatrix} x \\ y \\ z \end{pmatrix}_T = \begin{pmatrix} \Delta x \\ \Delta y \\ \Delta z \end{pmatrix} + (1 + \Delta s) \begin{pmatrix} 1 & -\omega_3 & \omega_2 \\ \omega_3 & 1 & -\omega_1 \\ -\omega_2 & \omega_1 & 1 \end{pmatrix} \begin{pmatrix} x \\ y \\ z \end{pmatrix}_S$$

EXAMPLE 3: Guideline d:

Note:

This transformation is widely used in geodesy with rotation angle values specified in arc second or milliarcsecond (mas) units.

13.3.5 Guidelines for registration of ORMTs

ORMTs shall be registered according to the following additional guidelines:

- A list of RDs that comprise the RD set shall be specified.
- The binding constraints shall specify the relationship(s) in object-space between two or more geometric constructions corresponding to RD bindings. These binding constraints shall be constructed so that any realization of the ORMT shall be an ORM.
- Additional, non-normative information concerning the RD may be supplied in the form of notes.

EXAMPLE 1 Guideline a: "RD 1. The oblate ellipsoid RD with major semi-axis a and minor semi-axis b^a , and "RD 2. [Z AXIS 3D](#)".

EXAMPLE 2 Guideline b: "The constructed directed line bound to RD 2 shall contain the centre of the constructed oblate ellipsoid bound to RD 1".

EXAMPLE 3 Guideline c: “The constructed directed line bound to RD 2 passing through the origin of the normal embedding uniquely determines the z -axis of the normal embedding”.

13.3.6 Guidelines for registration of ORMs

ORMs shall be registered according to the following additional guidelines:

- a) The commonly known or published name(s) as cited in the reference(s) shall be specified.
- b) The label of the reference ORM for the spatial object shall be specified as follows:
 - 1) If the reference ORM for this object is standardized or registered, the label of that ORM shall be specified.
 - 2) Otherwise, if the ORM is object-fixed for a physical object, the phrase “This is the reference ORM for” followed by the spatial object name shall be specified.
 - 3) If neither 1) or 2) apply, the string “none” shall be specified.
- c) Binding information shall be specified according to case.
 - 1) Case: If the ORM is object-fixed and the spatial object is a physical object, the date that the ORM component RDs were bound in object-space shall be specified. This case includes time-fixed instances of dynamic ORMs for a physical object.

If the spatial object is the Earth, and if Greenwich, UK is not contained in the x -positive xz -half-plane of the normal embedding, then the significant location contained in the x -positive xz -half-plane of the normal embedding shall be specified.
 - 2) Case: If the ORM is based on ORMT [BI_AXIS_ORIGIN_3D](#) and if the ORM binding complies with a standardized OBRS, the label of that OBRS shall be specified.
 - 3) Case: If the ORM is for an abstract object, the string “none” shall be specified.
- d) The approximate region of object-space to which the model applies, expressed as either a spatial extent or the description as specified in the reference, shall be specified.
- e) The label of the ORMT for this ORM shall be specified.
- f) The label of the ellipsoidal RD, if any; otherwise “n/a”.
- g) If the ORM is object-fixed, one or more reference transformations shall be specified in accordance with [13.3.7](#).

EXAMPLE Guideline e: ORMT [TRI_PLANE](#).

13.3.7 Guidelines for registration of RTs

RTs shall be registered according to the following additional guidelines:

- a) The label of the standardized or registered ORM that this RT transforms shall be specified.
- b) The label of an RT shall identify the associated ORM. When possible, an RT label should be formed by pre-pending the associated ORM label.
- c) A non-normative description of the extent and/or the spatial bounds of the region for which this reference transformation is applicable. Angles may be expressed in arcdegrees (°) in order to avoid a loss of precision.
- d) The label of the standardized or registered STT that is used to specify the transformation.

- e) The STT parameter values shall be specified by value or by reference as follows:
- 1) If by value, the values of the STT parameters specifying the reference transformation H_{SR} (see [Table 10.1](#)) shall be specified. These values may be followed by a measurement/modelling error estimate expressed in one of the following forms:
 - i) : assumed precise
 - ii) : σ <standard error>
 - iii) : \pm <tolerance>
 - iv) no error information following a parameter value indicates that the error estimate is unknown or unobtainable
 - 2) If by reference, a citation(s) for the values of the STT parameters specifying the reference transformation H_{SR} and associated error estimates may be specified in a form given in e.1.i - iv. Terms appearing in the references that are cited for a value shall be enclosed in brackets ({ }). Any parameter value that is not specified in the citation(s) shall be specified as in the “by value” case.
 - 3) A dynamic $H_{SR}(t)$ transformation may specify parameter values as functions of time.
 - 4) To avoid loss of precision, axis rotation angles (if applicable to the STT) may be expressed in arc seconds (") and, in cases of a large rotation, in arc degrees (°).
- f) The date the RT was specified or published shall be specified.

EXAMPLE Guideline d: $\Delta x = 12 : \sigma 5$, $\Delta y = -133 : \pm 25$, $\Delta z = 0$: assumed precise .

13.3.8 Guidelines for registration of OBRs

OBRs shall be registered according to the following additional guidelines:

- a) A descriptive name shall be specified.
- b) A set of spatial objects for which the binding rules apply shall be specified.
- c) The binding restrictions shall be specified.
- d) Optionally, figures that explain and illustrate the OBRs may be specified.

13.3.9 Guidelines for registration of SRFTs

SRFTs shall be registered according to the following additional guidelines:

- a) A short name as published or as commonly known, and an optional description shall be specified.
- b) The object or object type shall be specified as abstract or physical, and if physical, one of: the Earth, planet, satellite, or the Sun; and, optionally, any restrictions on the object.
- c) The ORM constraint shall specify criteria for applicable ORMs.
- d) The label of a standardized or registered CS, compatible with ORM constraints, shall be specified.

- e) Each of the CS coordinate-component names and/or symbols shall be specified as follows:
 - 1) SRF-specific names and/or symbols for the coordinate-component names and/or symbols, if any. If all coordinate-component names and symbols are same as the CS, the phrase “Same as the CS” shall be used.
 - 2) The vertical coordinate-component, if applicable, shall be designated.
- f) The SRFT parameters shall be specified as follows:
 - 1) CS and RD parameters, if any, and SRF parameters that are not specified by a CS parameter binding rule in (g).
 - 2) If no parameters are required, this element shall specify “none”.
- g) The CS parameter binding rules shall be specified as follows:
 - 1) Rules for binding CS and RD parameters.
 - 2) Rules for binding CS and SRF parameters.
 - 3) If no binding rules are required, this element shall specify “none”.
- h) The SRF region (see [8.3.2.4](#)) shall be specified as follows:
 - 1) An optional restriction of the domain of the CS to an SRF region may be specified.
 - 2) If an SRF region is specified, optionally an extended SRF region may also be specified.
 - 3) If both are unspecified, then there are no additional constraints on coordinates beyond those of the CS. This is indicated by the phrase “No additional restrictions”.
- i) The API base SRF class shall be specified as one of [BaseSRF2D](#), [BaseSRF3D](#), [BaseSRFwithTangentPlaneSurface](#), [BaseSRFwithEllipsoidalHeight](#), or [BaseSRFMapProjection](#).
- j) The API SRF class name shall be specified.
- k) If SRFT parameters are specified in (f), then an API SRF parameter structure shall be specified. If possible, an existing data type that is already defined in [Clause 11](#) of this International Standard shall be referenced. Otherwise, this element shall include the definition of the required parameter structure, along with any other necessary supporting data types that are not already specified in this International Standard or in a registered SRFT.
- l) The API coordinate structure shall be specified. If possible, an existing coordinate structure that is already defined in [11.5.7](#) of this International Standard shall be referenced. Otherwise, this element shall include the definition of the required coordinate structure, along with any other necessary supporting data types that are not already specified in this International Standard or in a registered SRFT.
- m) Additional, non-normative information such as a description, modelled region, intended use, and/or application domain may be supplied in the form of notes.

EXAMPLE 1 Guideline c: “Shall be derived from: ORMT [OBLATE_ELLIPSOID](#) or ORMT [SPHERE](#).”

EXAMPLE 2 Guideline d: CS “[EUCLIDEAN 3D](#)”.

EXAMPLE 3 Guideline e.1: “The same as the CS.” or “*u*: *x* (*x*), and *v*: *y* (*y*)”.

EXAMPLE 4 Guideline e.2: “Ellipsoidal height is the vertical coordinate-component.” or “*w*: height (*h*) is the vertical coordinate-component”.

EXAMPLE 5 Guideline f.1: " λ_{origin} : longitude of origin ($-\pi < \lambda_{\text{origin}} \leq \pi$)".

EXAMPLE 6 Guideline f.1: " u_F : false easting ($u_F \geq 0$)".

EXAMPLE 7 Guideline g.1: "CS parameters match RD values: Major semi-axis a , and eccentricity e ".

EXAMPLE 8 Guideline m: "When the object is the Earth, this SRF is referred to as a geocentric SRF."

13.3.10 Guidelines for registration of SRFs

SRFs shall be registered according to the following additional guidelines:

- a) A short name as published or as commonly known, and an optional description shall be specified.
- b) The label of the applicable SRF template shall be specified.
- c) The label of the applicable ORM shall be specified.
- d) The SRF region (see [8.3.2.4](#)) shall be specified as follows:
 - 1) An optional restriction of the domain of the CS to an SRF region may be specified.
 - 2) If an SRF region is specified, optionally an extended SRF region may also be specified.
 - 3) If both are unspecified, then there are no additional constraints on coordinates beyond those of the CS. This is indicated by the phrase "No additional restrictions".
- e) The parameter values shall specify values for all SRF template parameters by value or reference. If by reference, a citation(s) shall be specified for the parameter values.
- f) Additional, non-normative information such as a description, modelled region, intended use, and/or application domain may be supplied in the form of notes.

EXAMPLE 1 Guideline b: "SRFT [TRANSVERSE MERCATOR](#)".

EXAMPLE 2 Guideline c: "ORM [OSGB 1936](#)"

EXAMPLE 3 Guideline d: "SRF region description: Great Britain."

EXAMPLE 4 Guideline e: by value example:

"longitude of origin: $\lambda_{\text{origin}} = -8^\circ$
 latitude of origin: $\phi_{\text{origin}} = 53^\circ 30'$
 central scale: $k_0 = 0,999\ 820$
 false easting: $u_F = 600\ 000\ \text{m}$
 false northing: $v_F = 750\ 000\ \text{m}$ "

13.3.11 Guidelines for registration of SRF sets and their members

SRF sets shall be registered according to the following additional guidelines:

- a) The name as published or as commonly known shall be specified, and an optional description may be specified.
- b) The label of the applicable SRF template shall be specified.
- c) The ORM constraints shall be specified as follows:
 - 1) If a unique ORM is applicable, its label shall be specified.
 - 2) If more than a single ORM is applicable, the criteria for applicable ORMs shall be specified.

- d) An optional description of the region corresponding to the union of the SRF regions of all of the set members.
- e) The SRF set membership shall be specified as either:
 - 1) The set of members, by individual listing, or
 - 2) An algorithm generating all set members, including for each: an optional label, a short name, SRF region, parameter values, and notes. If any member is labelled, all members shall be labelled.
- f) Additional, non-normative information such as a description, modelled region, intended use, and/or application domain may be supplied in the form of notes.

EXAMPLE 1 Guideline b: "SRFT [TRANSVERSE MERCATOR](#)".

EXAMPLE 2 Guideline c.1: ORM "[N_AM_1983](#)".

EXAMPLE 3 Guideline c.2: "A global model [ERM](#) such as ORM [WGS_1984](#)".

EXAMPLE 4 Guideline d.1:

" SRF region specification:
 $0^{\circ} \leq \varphi < 84^{\circ}$ "

EXAMPLE 5 Guideline d.2:

" Extended SRF region specification:
 $-0,5^{\circ} \leq \varphi < 84,5^{\circ}$ "

EXAMPLE 6 Guideline e.2: See the specification of SRF set [GTRS GLOBAL COORDINATE SYSTEM](#).

EXAMPLE 7 Guideline f: "A set of two localized SRFs where only one SRF is used for each county in the state and no overlap is allowed."

SRF set members shall be registered according to the following additional guidelines:

- a) The label of the SRF set member shall be specified only if all SRF set member labels are specified.
- b) A short name as published or as commonly known, and an optional description shall be specified.
- c) The SRF region (see [8.3.2.4](#)) shall be specified as follows:
 - 1) An optional restriction of the domain of the SRF set to an SRF region may be specified.
 - 2) If an SRF region is specified, optionally an extended SRF region may also be specified.
 - 3) If both are unspecified, then there are no additional constraints on coordinates beyond those of the SRF set as a whole. This is indicated by the phrase "No additional restrictions".
- d) The parameter values shall specify values for all SRF parameters by value or reference. If by reference, a citation(s) shall be specified for the parameter values.
- e) Additional, non-normative information such as a description, modelled region, intended use, and/or application domain may be supplied in the form of notes.

These specifications shall be explicit by listing for all members, or they shall be implicit by algorithmic specification for all members.

EXAMPLE 8 Guideline a: "[ZONE XIX](#)".

EXAMPLE 9 Guideline b: "Central zone."

EXAMPLE 10 Guideline c.1:

" SRF region specification:
 $-180^{\circ} \leq \lambda < -174^{\circ}$
 $0^{\circ} \leq \varphi < 84^{\circ}$ "

EXAMPLE 11 Guideline c.2:

" Extended SRF region specification:
 $179,5^{\circ} \leq \lambda < -173,5^{\circ}$
 $-0,5^{\circ} \leq \varphi < 84,5^{\circ}$ "

EXAMPLE 12 Guideline d: specification by value:

" longitude of origin: $\lambda_{\text{origin}} = -177^{\circ}$
 latitude of origin: $\varphi_{\text{origin}} = 0^{\circ}$
 central scale: $k_0 = 0,999\ 6$
 False easting: $u_F = -500\ 000\ \text{m}$.
 False northing: $v_F = 0\ \text{m}$."

13.3.12 Guidelines for registration of DSSs

DSSs shall be registered according to the following additional guidelines:

- a) The description shall include the name as published or as commonly known.
- b) Whether the DSS is of global or local extent, relative to the relevant spatial object, shall be specified.
- c) Whether or not the DSS has a DSS model, and, if so, a reference to that DSS model shall be specified.
- d) Additional, non-normative information concerning the DSS may be supplied in the form of notes.

EXAMPLE 1 Guideline a: "[WGS](#) 84 EGM 96 geoid".

EXAMPLE 2 Guideline d: "The geopotential surface defined by the [WGS](#) 84 EGM 96 Earth gravity model (EGM) that is closely associated with the mean ocean surface."

13.3.13 Guidelines for registration of profiles

Profiles shall be registered according to the following additional guidelines:

- a) SRM profile labels shall conform to the guidelines in [13.2.2](#) and the following additional guidelines:
 - 1) Labels shall be of the form "SRM_e_a_XXXX_PROFILE", where "e_a" denotes the combination of the edition number and the highest-numbered amendment from which the content of the profile is obtained, and "XXXX" denotes a word or phrase that identifies the profile and results in a unique profile label.
 - 2) If no profile content is obtained from an amendment, "e_a" shall be specified as "e_0".
 - 3) "XXXX" may contain user-specific version numbering information.
- b) A non-empty subset of the standardized and registered ORMs shall be specified, such that each ORM in the subset shall be applicable to at least one SRFT as specified in guideline (c).
- c) A non-empty subset of standardized and registered SRFTs shall be specified, such that for each SRFT in the subset, there is at least one ORM as specified in guideline (b) that is applicable to that SRFT.

- d) A subset of the standardized and registered SRFs shall be specified, including only SRFs derived from SRFTs as specified in guideline (c), and specifying an ORM as specified in guideline (b). The string “none” shall denote an empty set.
- e) A subset of the standardized and registered SRF sets shall be specified, including only SRF sets derived from SRFTs as specified in guideline (c), and such that at least one ORM as specified in guideline (b) satisfies the ORM constraint of the SRF set. The string “none” shall denote an empty set.
- f) The subsets specified in guidelines (d) and (e) shall not both be empty.
- g) A subset of the standardized and registered DSSs shall be specified. The string “none” shall denote an empty set.
- h) Error criteria may be specified for one or more SRFTs, as follows:
 - 1) The label of the SRFT shall be specified. Multiple SRFT labels may be grouped together.
 - 2) The error bounds for the SRFT(s) shall be specified as follows:
 - i) The positional error bound, in metres, shall be specified.
 - ii) The directional error bound, in radians, shall be specified.
 - iii) The ratio error bound shall be specified.
 - iv) Error bounds for one or more subsets of the ORMs may also be specified.
 - 3) An accuracy domain template for the SRFT(s) shall be specified.

EXAMPLE 1 Guideline a: {ORM [WGS_1984](#)}.

EXAMPLE 2 Guideline b: {SRFT [CELESTIODETTIC](#)}.

EXAMPLE 3 Guideline c: {SRF [GEODETTIC_WGS_1984](#)}.

EXAMPLE 4 Guideline d: none.

EXAMPLE 5 Guideline f: {DSS [EGM96_GEOID](#)}.

EXAMPLE 6 Guideline g.1: SRFT [CELESTIODETTIC](#).

EXAMPLE 7 Guideline g.2: $\varepsilon_P = 0,001\text{m}$, $\varepsilon_D = 0,000\ 1$, $\varepsilon_R = 0,000\ 1$. Oblate ellipsoid ORMs restricted to ellipsoid RDs with $a \leq 6\ 400\ 000$ and $f \leq 1/150$.

EXAMPLE 8 Guideline g.3: $-50\ 000, 0 \leq h \leq +1\ 000\ 000$.

<http://standards.iso.org/ittf/PubliclyAvailableStandards/>